



NOTES:

1. CONCRETE CURB SHALL NOT ENCR OACH INTO PUBLIC RIGHT-OF-WAY AND SHALL BE FLUSH AT BACK OF WALK.
2. COMMERCIAL DRIVEWAY SHALL BE INSTALLED IN ZONES DESIGNATED COMMERCIAL, INDUSTRIAL, AND RESIDENTIAL WITH 4 UNITS OR MORE.
3. 18" WIDE BAND OF PAVEMENT SHALL BE REMOVED AND REPLACED. SEE NOTE 5 OF GENERAL NOTES (APPENDIX A) FOR REQUIREMENTS.
4. WHERE THE DISTANCE BETWEEN NEW DRIVEWAY LIMIT AND PROPERTY LINE IS LESS THAN 6 FEET AT THE BACK OF DRIVEWAY AND THERE IS AN ADJACENT DRIVEWAY LESS THAN 12 FEET DISTANCE AWAY, THE SIDEWALK SHALL NOT TRANSITION. NEW SIDEWALK SHALL TERMINATE AT PROPERTY LINE.
5. WHERE THE DISTANCE BETWEEN NEW DRIVEWAY AND PROPERTY LINE IS EQUAL TO OR GREATER THAN 6 FEET AT THE BACK OF DRIVEWAY AND THERE IS NO ADJACENT DRIVEWAY WITHIN 12 FEET DISTANCE OF NEW DRIVEWAY, THE SIDEWALK SHALL TRANSITION FROM BACK OF DRIVEWAY TO EXISTING SIDEWALK.
6. JOINT/SCORE MARK TABLE:

DRIVEWAY WIDTH		WEAKENED PLANE JOINT		SCORE MARKS	
MIN.	MAX.	NO. OF JOINTS	LOCATION POINT	NO. OF MARKS	LOCATION POINT
24'	30'	2		3	1/6, 1/2, 5/6
>30'	40'	3	1/4, 1/2, 3/4	4	1/8, 3/8, 5/8, 7/8
>40'	50'	4	1/5, 2/5, 3/5, 4/5	5	1/10, 3/10, 1/2, 7/10, 9/10

SCORE MARK REQUIRED AT DRIVEWAY SLOPE BREAK PARALLEL TO EXISTING FACE OF CURB



DRAWN BY: M. LEE
 CHECKED BY: S. THACH
 APPROVED BY: T. SUPAN
 DATE: JANUARY 2007

COMMERCIAL DRIVEWAY WITH ATTACHED SIDEWALK

CITY OF SANTA CLARA

ST-5

PAGE: 5